
Mini double-loop paper bow


pap-147 / A4 / Parts overview - NOT A CUTTING SHEET

USE THE FOLLOWING PATTERN SHEETS AT ACTUAL SIZE.

These miniature views identify the supplied patterns; they are deliberately reduced.



1. Pattern 1




2. Pattern 2

2 pattern sheets supplied. Printed details are not cut lines unless explicitly marked.

Solid cut boundary / dashed score / shaded joining area. Read the full instructions.

Dry-fit the parts before gluing. Keep this overview beside the full-size pattern sheets.




50 mm print check

Print at actual size / 100%. Disable fit-to-page.
Use the paper edition that matches the printer tray.


Mini double-loop paper bow

pap-147 / A4 / Pattern 1


Bow loop 1




Bow loop 2



Bow loop 3



Bow loop 4



50 mm print check


Print at actual size / 100%. Disable fit-to-page.

Use the paper edition that matches the printer tray.

Mini double-loop paper bow

pap-147 / A4 / Pattern 2

Bow center band and tails



50 mm print check

Print at actual size / 100%. Disable fit-to-page.

Use the paper edition that matches the printer tray.

Mini double-loop paper bow

pap-147 / A4 / Instructions

PURPOSE

Mini double-loop paper bow developed as a measured original paper study. The packet provides the actual parts, joining or shaping marks, drawing dimensions and an assembly sequence. Print at actual size and dry-fit the parts before gluing.

DRAWING FACTS

- 4 shaped loop strips, center band 60 x 16 mm, 94 mm tail piece.

MATERIALS


Plain 100 to 140 gsm paper for a first dimensional trial; approximately 160 to 220 gsm card only after confirming the folds. Use a ruler, suitable scissors, a blunt scoring tool and a small amount of paper adhesive. An adult should handle internal cuts, holes and small fasteners.

HOW TO USE THESE PAGES

1. Bring each loop strip end inward to meet at its center without creasing the rounded loop.
2. Bond each strip's short ends at its center. Cross loops 1 and 2; cross loops 3 and 4 at their joined centers.
3. Stack the two pairs at their centers. Place the notched tail behind them, then wrap the narrow band around the center.
4. Allow the center to set. Attach to a dry paper surface with an appropriate removable fixing.

LIMITS AND CHECKS

- Drawing dimensions describe flat paper surfaces, not verified internal capacity, load strength, fit or material compatibility.
- No mailing, food-contact, archival, toy-safety, protective-wear or cutting-machine certification is supplied.
- Make a plain-paper trial first; paper thickness and fold accuracy can change the fit.
- Trial: Measure the 50 mm reference and two named component dimensions.
- Trial: Make a complete empty trial and document fold direction, joining order, collision, stability and any fragile features.
- Trial: Repeat the trial using your chosen paper. Check that every join holds and each moving part works freely before decorating.



Print at actual size / 100%. Disable fit-to-page.

Use the paper edition that matches the printer tray.